# Galvanized Alternate Tread Stair 68 Degrees 63-1/2 In. x 23-1/2 In. x 173-5/8 In. 350 Lb. Capacity Silver

**MODEL ATS-11-68-HDG**

Industrial Ladders / Alternating-Tread Stairs

## PRODUCT OVERVIEW

Alternating-tread stair design is a great addition to a variety of warehouses and workshops. The unique design offers a shorter span than traditional steps. With a handrail on each side of unit and a dual safety chain at the top of the stair, security is the top priority of this ladder style.

## KEY FEATURES

- Two-sided hand railing provides added user safety
- Steps are constructed of a raised steel surface providing better traction
- Handrails have a safety yellow powder coat finish
- Steel steps and platform have a durable hot dip galvanize finish

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 249 lbs | 23.5" W x 63.5" L x 173.625" H | 298 lbs |
| **PACKAGE 1 SIZE** | **COLOR / FINISH** | **FREIGHT TYPE** |
| 32" W x 144" D x 19" H | Silver | LTL Palletized |

**AVAILABILITY** Quote Required - Please Contact Sales **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 350 |
| **Number of Steps** | 17 |
| **Top Step Height (in.)** | 131-3/4 |
| **Step Angle (degrees)** | 68 |
| **Safety Chain (in.)** | 3/16 |
| **Top Step Depth (in.)** | 9-3/4 |
| **Top Step Width (in.)** | 23-5/8 |
| **Step (excluding top step) Depth (in.)** | 10-1/2 |
| **Step (excluding top step) Width (in.)** | 9-1/8 |
| **Step Height Spacing (in.)** | 7-3/4 |
| **Handrail Height (in.)** | 12-1/4 |
| **OSHA** | 29 CFR 1910.25(e`) |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?PID=612