# Steel Alternate Tread Stair 68 Degrees 34-5/8 In. x 23-1/2 In. x 101-7/8 In. 350 Lb. Capacity Yellow

**MODEL ATS-5-68**

Industrial Ladders / Alternating-Tread Stairs

## PRODUCT OVERVIEW

Alternating-tread stair design is a great addition to a variety of warehouses and workshops. The unique design offers a shorter span than traditional steps. With a handrail on each side of unit and a dual safety chain at the top of the stair, security is the top priority of this ladder style.

## KEY FEATURES

- Two-sided hand railing provides added user safety
- Raised steel surface provides better traction
- Powder coat finish for baked in toughness
- Durable steel construction

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 138 lbs | 23.5" W x 34.625" L x 101.875" H | 190 lbs |
| **PACKAGE 1 SIZE** | **COLOR / FINISH** | **FREIGHT TYPE** |
| 40" W x 64" D x 16" H | Yellow | LTL Palletized |

**AVAILABILITY** Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 350 |
| **Number of Steps** | 8 |
| **Top Step Height (in.)** | 60 |
| **Step Angle (degrees)** | 68 |
| **Safety Chain (in.)** | 3/16 |
| **Top Step Depth (in.)** | 9-3/4 |
| **Top Step Width (in.)** | 23-5/8 |
| **Step (excluding top step) Depth (in.)** | 10-1/2 |
| **Step (excluding top step) Width (in.)** | 9-1/8 |
| **Step Height Spacing (in.)** | 7-1/2 |
| **Handrail Height (in.)** | 12-1/4 |
| **OSHA** | 29 CFR 1910.25(e`) |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?PID=612