

# Aluminum Truck Dock Board 66 In. x 54 In. 7000 Lb. Capacity Silver

**MODEL BTA-07006654**

Loading Dock Equipment / Aluminum Truck Dockboards (Welded Aluminum Curbs)

## PRODUCT OVERVIEW

The Aluminum truck dock board is engineered and built to maximize safety while handling heavy fork trucks and loads. Locking legs prevent movement during loading and unloading operations. Locking legs are uneven to allow the dock board to sit canted, while not in use, for easier pickup by fork trucks. Welded aluminum safety curbs prevent accidental runoffs and provide visible driving lane. When using three-wheeled fork trucks order dock board with capacity at least four-times the lifting capacity of fork truck. The width of the dock board should be at least 15 (in.) wider than the load or equipment passing between the curbs. Bend is 11 degrees and 9" from the edge and the legs are 12" from the edge. Manufactured in compliance with OSHA.

## KEY FEATURES

- 100% Aluminum construction provides rugged long lasting use
- Raised-diamond tread plate dock board surface
- Welded aluminum locking legs underneath dock board
- Beveled entry and exit edges provide a smooth transition

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**144 lbs**

ASSEMBLED SIZE  
**66" W x 54" L x 13.75" H**

SHIP WEIGHT  
**144 lbs**

PACKAGE 1 SIZE  
**66" W x 54" D x 16" H**

COLOR / FINISH  
**Silver**

FREIGHT TYPE  
**LTL Loose**

**AVAILABILITY** Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                                |                              |
|------------------------------------------------|------------------------------|
| Uniform Capacity (lb.)                         | 7000                         |
| Height Difference (in.): 8 degree/17 percent   | 6                            |
| Height Difference (in.): 11 degrees/19 percent | 8-1/2                        |
| Bend Degree                                    | 11                           |
| Bend Distance from Edge (in.)                  | 9                            |
| Leg Distance from Edge (in.)                   | 12                           |
| Usable Width (in.)                             | 61-1/2                       |
| Usable Length (in.)                            | 54                           |
| Edge Type                                      | Beveled                      |
| Equipped With                                  | Welded Aluminum Locking Legs |
| Surface Type                                   | Raised-Diamond Treadplate    |
| Plate Thickness (in.)                          | 3/8                          |
| Curb Height (in.)                              | 2-3/4                        |
| Curb Width (in.)                               | 2-1/4                        |
| OSHA                                           | 1910.30 (a)                  |
| ANSI                                           | MH 30.2                      |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=33>