

# Steel Electric Hydraulic Dock Leveler 74"W x 86"L x 24"D Pit Dimensions, 25000 Lb. Capacity Brown/Yellow

**MODEL EH-68-25**

Loading Dock Equipment / Electric Hydraulic Dock Levelers

## PRODUCT OVERVIEW

The electric hydraulic dock leveler is ideal for high usage dock areas. The hydraulic design is state of the art and consists of a single button operation. The operator pushes and holds the "raise" button which activates the hydraulic pump and raises the deck. When the deck reaches the raised position the lip automatically extends. The operator releases the "raise" button and the deck descends to rest on the trailer. The control box includes a red emergency stop button standard. When the truck pulls away, the deck descends to full down position, trips the limit switch and returns automatically to the level cross traffic position. It includes telescopic steel toe guards on both sides, flush with platform edge and includes two (2) laminated bumpers.

## KEY FEATURES

- State of the art design consists of a push button operation
- Control box includes a red emergency stop button
- Returns automatically to the level cross traffic position
- Includes telescopic steel toe guards and two laminated bumpers

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**1907 lbs**
**ASSEMBLED SIZE**  
**23.5" W x 86" L x 72" H**
**SHIP WEIGHT**  
**2129 lbs**
**PACKAGE 1 SIZE**  
**72" W x 86" D x 24" H**
**COLOR / FINISH**  
**Brown / Yellow**
**FREIGHT TYPE**  
**LTL Loose**
**AVAILABILITY**      Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP: --**

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| Uniform Capacity (lb.)         | 25,000                                             |
| Service Range Above Dock (in.) | 12                                                 |
| Service Range Below Dock (in.) | 12                                                 |
| Voltage/Phase                  | 460/3                                              |
| Platform Thickness (in.)       | 1/4                                                |
| Motor Horsepower               | 2                                                  |
| Installation Type              | Crew must install (due to electrical requirements) |
| Laminated Bumper Length (in.)  | 4.5                                                |
| Laminated Bumper Width (in.)   | 14                                                 |
| Laminated Bumper Height (in.)  | 10                                                 |
| Unit Width (in.)               | 72                                                 |
| Unit Depth (in.)               | 23-1/2                                             |
| Unit Length (in.)              | 86                                                 |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA