

# Steel Electric Hydraulic Dock Leveler 86"W x 110"L x 24"D Pit Dimensions, 45000 Lb. Capacity Brown/Yellow

**MODEL EH-710-45**

Loading Dock Equipment / Electric Hydraulic Dock Levelers



## PRODUCT OVERVIEW

The electric hydraulic dock leveler is ideal for high usage dock areas. The hydraulic design is state of the art and consists of a single button operation. The operator pushes and holds the "raise" button which activates the hydraulic pump and raises the deck. When the deck reaches the raised position the lip automatically extends. The operator releases the "raise" button and the deck descends to rest on the trailer. The control box includes a red emergency stop button standard. When the truck pulls away, the deck descends to full down position, trips the limit switch and returns automatically to the level cross traffic position. It includes telescopic steel toe guards on both sides, flush with platform edge and includes two (2) laminated bumpers.

## KEY FEATURES

- Hydraulic design is state of the art with simple push button operation
- When the deck is raised lip automatically extends for easy loading/unloading
- Control box includes a red emergency stop button for optimal safety
- Features telescopic steel toe guards on both sides for added safety

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**3143 lbs**

ASSEMBLED SIZE  
**23.5" W x 110" L x 84" H**

SHIP WEIGHT  
**3667 lbs**

PACKAGE 1 SIZE  
**86" W x 110" D x 48" H**

COLOR / FINISH  
**Brown / Yellow**

FREIGHT TYPE  
**Flatbed Required**

AVAILABILITY      Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| Uniform Capacity (lb.)         | 45,000                                             |
| Service Range Above Dock (in.) | 12                                                 |
| Service Range Below Dock (in.) | 12                                                 |
| Voltage/Phase                  | 460/3                                              |
| Platform Thickness (in.)       | 3/8                                                |
| Motor Horsepower               | 2                                                  |
| Installation Type              | Crew must install (due to electrical requirements) |
| Laminated Bumper Length (in.)  | 4.5                                                |
| Laminated Bumper Width (in.)   | 14                                                 |
| Laminated Bumper Height (in.)  | 10                                                 |
| Unit Width (in.)               | 84                                                 |
| Unit Depth (in.)               | 23-1/2                                             |
| Unit Length (in.)              | 110                                                |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA