

Steel Dock Safety Swing Gate 2 Ft. Length Yellow

MODEL SSG-2

Loading Dock Equipment / Economical Safety Swing Gates

PRODUCT OVERVIEW

Economical safety swing gates are an economical way to protect people from dock falls. Durable railings are constructed from schedule 10 pipe (1-5/8" O.D.). Units have a top rail height of 46-1/4" and a 25" mid-rail. 4" poly-on-poly wheel allows units to be swung out of the way. Cast single socket is included.

KEY FEATURES

- Ideal for loading docks, floor openings, and mezzanines
- Pre-drilled base plate mounting holes
- Yellow powder coat finish
- Foot release lock keeps railing from moving when in use

CORE PRODUCT DATA

ASSEMBLED WEIGHT 30 lbs	ASSEMBLED SIZE 6.5" W x 28.0625" L x 46.25" H	SHIP WEIGHT 31 lbs
PACKAGE 1 SIZE 24" W x 2" D x 42" H	COLOR / FINISH Yellow / Blue	FREIGHT TYPE Parcel
AVAILABILITY Available Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.		QUICKSHIP: YES

PRODUCT SPECIFICATIONS

Hardware Included	Yes
Base Plate Mounting Hole Qty	4
Base Plate LxW (in.)	4-1/2 x 4-1/2
Base Plate Mounting Hole Diameter (in.)	3/8
Base Plate Thickness (in.)	1/4
Handrail LxH (in.)	24 x 46-1/4
Midrail Height (in.)	25-3/4
Rigid Caster (qty.)	1
Rigid Caster Diameter (in.)	4
Rigid Caster Width (in.)	1-1/4
Caster Material	Polyurethane
Caster Color	Black

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=11>