Galvanized Steel AC Powered Jib Crane CSA Compliant 3-1/2 to 5-1/2 Ft. Boom 1,500 lb. Capacity Gray

MODEL WTJ-E-15-3-AC-CSA-GA

Overhead Lifting / Power Lift Jib Cranes

PRODUCT OVERVIEW

The power lift Jib cranes are designed for material handling applications on docks, in warehouses or in truck beds. Choose either 12V DC, 1 HP with 6-foot long removable pendant control or 115V AC 1/3 HP with fingertip switch to raise and lower hook. Meets ANSI and OSHA specifications. 12" x 12" mounting plate. Units are not rated for overhead lifting applications. Consult factory for pricing if overhead lifting rating is required. Intermittent use cranes feature rotation hand brakes that offer unlimited 360 degrees positioning. Mast mounts permanently. Boom adjusts in 12" increments and can be positioned at 4 elevations. The AC units feature 25 feet of 7/32" cable. Folds for storage.

KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

CORE PRODUCT DATA

ASSEMBLED WEIGHT	ASSEMBLED SIZE	SHIP WEIGHT
176 lbs	18.6875" W x 66.75" L x 67.5" H	223 lbs

PACKAGE 1 SIZE	COLOR / FINISH	FREIGHT TYPE
29" W x 66" D x 17" H	Gray	LTL Palletized

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	1500
Boom Reach (in.)	43-1/16 to 66-3/4
Boom Height (in.)	47-1/8 to 73-5/16
Rotation Degree	360
Boom Adjustment Increments (in.)	12
Cable Length (ft.)	25
Cable Diameter (in.)	7/32
AC (volts)	115
Horsepower (HP)	1/3
Mounting Plate Length (in.)	12
Mounting Plate Width (in.)	12
1,500 lb. Capacity at Boom Extension (in.)	27-13/16
Capacity at 47-1/8" Fully Retracted (lbs.)	650
Capacity at 47-1/8" Mid-Position (lbs.)	300
Capacity at 47-1/8" Fully Extended (lbs.)	200
Capacity at 56-3/16" Fully Retracted (lbs.)	1100
Capacity at 56-3/16" Mid-Position (lbs.)	650
Capacity at 56-3/16" Fully Extended (lbs.)	550
Capacity at 64-3/4" Fully Retracted (lbs.)	1,250
Capacity at 64-3/4" Mid-Position (lbs.)	850
Capacity at 64-3/4" Fully Extended (lbs.)	650
Capacity at 73-5/16" Fully Retracted (lbs.)	1500
Capacity at 73-5/16" Mid-Position (lbs.)	1150
Capacity at 73-5/16" Fully Extended (lbs.)	800
Compliant	CSA

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?FID=582